

SPECIFICATIONS


ELECTRICAL:

| | |
|------------------------|------------------------|
| Contact Resistance: | 40 milli Ohms max. |
| Insulation Resistance: | 1000 M Ohms min. 500 |
| Proof Voltage: | 1000 V AC for 1 minute |

MECHANICAL:

| | |
|-------------------|-------------------------------------|
| Housing: | PBT Glass filled UL94V0 |
| Contact Material: | Phosphor Bronze 0.46 dia. |
| Contact Plating: | Gold Plating 03, 06, 15, 30 or 50U" |
| Operating Life: | 600 mating cycles min. |

Part No: JP-LP-6P2C / 6P4C / 6P6C

| | | | |
|--|----------------------|--|---------------|
| Part Name: | Material: | Revision No: 00 | Sheet 1 of 1 |
| 1. Housing | PBT UL94V0 | Design by: PRM | Date: 04/5/04 |
| 2. Contact Pins | PhBz Gold Plated | Checked by: APM | Date: 04/5/04 |
| Main Product: LOW PROFILE SIDE ENTRY MOD. JACK | | Approved by: APM | Date: 04/5/04 |
| Tolerance: ± 0.2 mm | Scale: Not to scale | Drawing No: | |
| Dimensions: mm | 3rd Angle Projection |  PRAN ELECTRONICS PVT. LTD. 52 GIDC MAKARPURA VADODARA 390 010 | |