


PCB MOUNTING HOLE LAYOUT



CIRCUIT DIAGRAM

OP. FORCE	LONG LIFE	
	code	cycles
gf		
160	2	-
180/200	5	1KK. M
250	3	500K. 5

Part No:60-5SX0-Y
Waterproof

SPECIFICATIONS

- CONTACT : METAL CONTACT
- RATING : 50mA X 12V DC
- CONTACT RESISTANCE : 100 mΩMAX
- PROOF VOLTAGE : 250 V AC FOR 1 MIN
- INSULATION RESISTANCE : 100 MΩMIN/100 V DC
- OPERATING FORCE : 160±30 gf, 250±50 gf
- OPERATING LIFE : 100,000 CYCLES

WATERPROOF PROPERTIES

- TEMPERATURE : 60 deg C
- WATER DEPTH : 10 CM
- TIME : 240HR
- HUMIDITY : 90/95% - 100HRS

Part Name:	Material:	Revision No: 00	Sheet 1 of 1
		Design by:	Date:21/11/03
		Checked by:	Date:21/11/03
		Approved by:	Date:21/11/03
Main Product: Tact Switch - Waterproof		Drawing No:60-5SX0	
Tolerance:± 0.2mm		Scale: Not to scale	
Dimensions: mm.		3rd Angle Projection	
		Pran Electronics Pvt. Ltd.	
		52 G.I.D.C. Makarpura Vadodra 390 010. INDIA	
		Phone:02651263 2916/5920. Fax: 263 5918.	
		Email: info@pranelectronics.com	